

# Semi-Automatic L-Type Sealing Machine

AP-1622A/AP-1622AP/AP-2028A/AP-2028AP/AP-3040A/AP-3040AP/AP-4048AP

This machine is an economic solution for packaging of any solid product. It may couple with APT-1810 Heat Shrink Tunnel to form a completed packaging line.



AP1622AP+APT-1810 Heat Shrink Tunnel



Stainless Steel Compensator Assembly allows operator to adjust wire temperature, unit compensates for residual heat in wire from previous cycle. Precise control of heat means consistent seals every cycle.

Teflon Coated Ceramic "V" Groove Beads under seal wire are designed to withstand high sealing temperatures and provides the highest quality and most consistent seals every time.

Pin Wheel Hole Punch : Places multiple rows of holes to allow air evacuation from package.



AP-1622A

## Feature

1. Anti-adhesive Teflon Coated Sealing Blade ensures neat and firm seal without smoke pollution. Overheat protect function extends the lifespan; hand clamping protect device avoids mistakenly damaging the product and also for the safety of the operator.
2. Dual magnet clamping increases the sealing force ensuring a firm seal.
3. Easy adjustment of sealing and conveyor time.
4. Quick film loading Design and advanced pin perforation device.
5. Selected electrical components from reliable international manufacturer.
6. Heavy duty castor with lock device makes an easy move and locate.
7. AP-1622AP Type, Pneumatic Cylinder Type Sealer offers Manual and Auto Mode for operation. The whole sealing cycle is done by cylinder, which lessens power of work and improves efficiency.

## SPECIFICATION

Model No.	AP-1622A	AP-1622AP	AP -2028A	AP-2028AP	AP -3040A	AP-3040AP	AP-4048AP
Max Sealing size	550X400	550X400	700X500	700X500	1000X750	1000X750	1200X1000
Voltage	220V/1ph						
Compress Air	--	0.6MPA	--	0.6MPA	--	0.6MPA	0.6MPA
Machine Size(LXWXH)	1600X775X1000	1600X775X1100	1900X875X1000	1900X875X1100	2500X1125X1000	2500X1125X1100	2910X1300X1100
Packed machine size (Lx W x H)	1410X760X1170	1410X760X1170	1710X860X1180	1710X860X1180	2310X1210X1270	2310X1210X1270	3020X1490X1320
Equipment weight (Kg)	145/190	145/190	210/265	210/265	345/440	345/440	680/880

※Special size available on request