# **Heat Shrink Tunnel**

### APT-1810/APT-2212/APT-1810/2/APT-2816/2





LA-460E + APT-1810







#### **Application**

An industrial heat shrink tunnel use heat to shrink film around packages. This machine is designed to work with L bar sealer or sleeve wrapper bundler, but also stand alone for shrink banding applications, is compatible with a wide range of standard product sizes and offer optimum shrink performance while using minimum space.

#### **Standard Feature**

- 1. Adopt solid stainless steel heater, durable with low power consumption.
- 2. Digital Temperature Controller.
- 3. Conveyor speed adjustable.
- 4. Live Roller Rod Conveyor adopts durable solid roll outer coated with silicone rubber to prevent dust and stand fire. (Option: Teflon Mesh Overlay Conveyor)
- Automatic Shutting-Off Function can automatically switch off the power when the tunnel temperature drops below 70°C, ensuring maximum life span and saving the waiting time.
- 6. Selected electrical components from reliable manufacturer.
- 7. Easy adjustment of tunnel height to suit products in various heights.







Compliance with CE & UL Standard

All major parts use foreign product.

## **Specification**

Model No.	APT-1810	APT-2212	APT-1810/2	APT-2816/2
Tunnel Size	1000X450X250	1200X550X300	1800X450X250	1800X700X400
Voltage	380V/3ph	380V/3ph	380V/3ph	380V/3ph
Power	10Kw	10Kw	20Kw	24Kw
Machine Size	1655X830X1555	1850X930X1600	2455X1020X1530	2455X1080X1700
Coupling L Sealer	AP-1622A	AP-2028A	APSS-5022 or LA-460	APSS-7522 or LA-680
Packed machine size (Lx WxH)	1650X880X1070	1860X980X1130	2590X1150X1770	2300X1410X2000
Machine weight (NW/GW)	250/320 kg	300/365 kg	450/550 kg	700/880 kg



歐華包裝企業有限公司

## Alpha-Pack Enterprise Ltd.

leading specialist of packaging machinery manufacturer
Unit 1406 Vanta Industrial Center
21-23 Tai Li Pai Road, Kwai Chung, Hong Kong
Tel: (852) 2416 1237 Fax: (852) 2264 6540





